

Section 1: Manufacturer and Product Identification

Supplier/Distributor: Truck-Lite Co., LLC 310 East Elmwood Avenue Falconer, NY 14733 **Product Information:** nanoSealTM Dielectric Gel

Recommended Use: Industrial Dielectric Lubricant

Manufacturer/ SDS Preparer: NanoMech, Inc. Springdale, Arkansas 72764 Phone: (479) 725-8003

Emergency Phone: 1-800-424-9300

Section 2: Hazards Identification

Hazard Classification: Health Hazards: Skin Corrosion/Irritation Eye Damage/Irritation

Warning Label Items:

Pictogram(s):



Signal Word(s): WARNING

Hazard Statement(s):

Causes skin irritation. Causes eye irritation. Category 2 Category 2B

Precautionary Statement(s):

Wash exposed areas that have come in contact with material thoroughly after handling. Wear protective gloves.

If on skin: wash with plenty of water.

Specific treatment (see first aid measures on this SDS).

If skin irritation occurs: get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If in eyes: rinse cautiously for water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: get medical advice/attention.

Hazards Not Otherwise Classified:

None known.

Percentage of Ingredients with Unknown Toxicity:

Zero

Section 3: Composition/Information on Ingredients¹

Component A Component B **Chemical Identity** Synthetic Fluoropolymer Inorganic Silica-Based Grease Mixture **Concentration (%)** 0 – 10 90 – 100

The specific chemical identities and exact percentages (concentrations) of the ingredients of the composition have been withheld as trade secrets.

Section 4: First-aid Measures

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Seek immediate medical advice if breathing difficulties continue.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. If symptoms persist, get medical attention.

After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, get medical attention.

¹The composition of nanoShellTM Dielectric Enamel (both component identities and percentages) is confidential to NanoMech, Inc. and should only be disclosed to company employees as needed to comply with OSHA's Hazard Communication Standard.

After ingestion:

Get medical attention if symptoms occur. Do not induce vomiting.

Most important symptoms/effects, acute and delayed:

Causes skin and eye irritation.

Immediate medical attention required:

None needed.

Section 5: Fire-fighting Measures

Flammability:

May burn, but does not ignite readily.

Means of Extinction:

Use dry chemical, foam, halon, or CO₂. Move container from fire area if you can do it without risk. Apply cold water to sides of container that are exposed to flames until well after the fire is out. Keep distance from the fire and the container.

Flashpoint (°C):

315°C (ASTM D-92)

Upper Flammability Limit (% by volume):

Not determined

Lower Flammability Limit (% by volume): Not determined

Autoignition Temperature (°C): >300°C

Explosion Data – Sensitivity to Impact: Not determined

Explosion Data – Sensitivity to Static Discharge: Not determined

Hazardous combustion products: Oxides of carbon, smoke, and irritating vapors

Protective equipment:

Wear self-contained respirator. Wear fully protective impervious suit.

Section 6: Accidental Release Measures

Small spills:

Absorb with diatomaceous earth, sand or other non-combustible material and transfer to containers for later disposal. Use clean non-sparking tools to collect absorbed material.

Large spills:

Enclose the spill area for later disposal.

Person related safety precautions:

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

Measures for environmental protection:

Do not allow material to be released to the environment without proper governmental permits.

Measures for cleaning/collecting:

Ensure adequate ventilation.

Section 7: Handling and Storage

Handling

Information for safe handling:

Keep container tightly sealed. Slowly open the container. Ensure good ventilation at the workplace.

Storage

Requirements to be met by storerooms and receptacles:

Store in cool, dry place in tightly closed containers. Keep away from freezing. Protect material from direct sunlight.

Information about storage in one common storage facility:

Store away from strong acids and oxidizing agents.

Section 8: Exposure Controls and Personal Protection

Chemical Identity	ACGIH TLV	OSHA PEL
Component A	10 mg/m ³ TWA	15 mg/m ³ TWA
Component B	None	20 million particles/foot ³ TWA

Specific Engineering Controls:

Provide sufficient mechanical ventilation to maintain exposure below TLV(s). Overexposures to vapors and mists may be prevented by ensuring ventilation controls, local exhaust and/or fresh air entry.

Eye Protection:

Vapor tight chemical-type splash goggles should be worn when the possibility exists for eye contact due to splashing or spraying of liquid or the generation of airborne particles or vapors.

Skin Protection:

Wear protective clothing.

General Protective and Hygienic Measures:

The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Remove all soiled and contaminated clothing immediately. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

Respiratory Protection:

Use NIOSH-approved respirator if there is potential to exceed exposure limits.

Protection of Hands:

Wear impervious gloves. Check protective gloves prior to each use for their proper condition. The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Section 9: Physical and Chemical Properties

General Information

Physical state: Paste Color/Appearance: White **Odor:** Moderate Odor threshold: Not determined Specific Gravity: 1.06 Vapor density: Not determined Vapor pressure: Not determined Evaporation rate: Not determined Boiling point: Not determined Freezing point: Not determined **pH:** Not determined Coefficient of Water/Oil Distribution: Not determined Melting point/Melting range: Not determined Sublimation temperature/start: Not determined Flash point: 315°C Autoignition temperature: >300°C **Decomposition temperature:** Not determined Danger of explosion: Product does not present an explosion hazard Flammability limits: **Lower:** Not determined **Upper:** Not determined

Solubility in/Miscibility with Water: Insoluble Viscosity: 350 cSt

Section 10: Stability and Reactivity

Reactivity:

Not reactive if used and stored according to specifications.

Chemical Stability:

Stable under normal conditions.

Possibility of Hazardous Reactions:

Dangerous reactions and decomposition will not occur if used and stored according to specifications.

Conditions to Avoid:

Keep away from freezing. Protect material from direct sunlight, open flames, hot surfaces, and sources of ignition. Store away from strong acids and oxidizing agents.

Incompatibility with Other Substances:

Strong acids and oxidizing agents.

Hazardous Decomposition Products:

Oxides of carbon, smoke, and irritating vapors.

Section 11: Toxicological Information

Effects of Acute Exposure:

Slightly irritating to skin, eyes, and respiratory tract.

Effects of Chronic Exposure:

No known significant chronic effects.

Irritancy of Product:

Slightly irritating to skin and eyes.

Skin and Respiratory Sensitization:

No known sensitizing effects.

Carcinogenicity (NTP, IARC, ACGIH or OSHA):

None of the components are classified as carcinogens by NTP, IARC, ACGIH or OSHA.

Reproductive Toxicity:

No known reproductive effects.

Teratogenicity:

No known teratogenic effects.

Embryotoxicity:

No known embryotoxic effects.

Mutagenicity:

No known mutagenic effects.

Name of Synergistic Products/Effects:

None known.

Acute toxicity:

LD/LC50 values that are relevant for classification: Oral: LD: Not Determined Dermal: LD: Not Determined Inhalative: LC50/4H: Not Determined

Section 12: Ecological Information

General notes:

Do not release material to the environment without proper governmental permits.

Section 13: Disposal Considerations

General notes:

Consult state, local or national regulations to ensure proper disposal. Disposal must be made according to official regulations.

Section 14: Transport Information

Special Shipping Information: Not regulated. DOT regulations: Hazard Class: None Land transport ADR/RID (cross-border) ADR/RID Class: None Maritime transport IMDG: IMDG Class: None Air transport ICAO-TI and IATA-DGR: ICAO/IATA Class: None

Transport/Additional information:

Not dangerous according to the above specifications. Keep separated from foodstuff.

Section 15: Regulatory Information

National Regulations:

All components of this product are listed on the TSCA Inventory or are exempt.

WHMIS Classification:

D2B.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

Information about limitation of use:

For use only by technically qualified individuals.

Section 16: Other Information

Hazardous Material Identification System (HMIS) Classification:

Health:	1
Flammability:	1
Reactivity:	0

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgment of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Contact:

Mr. Wyatt Watkins NanoMech, Inc. 2447 Technology Way Springdale, Arkansas 72764 **Phone:** (479) 695-8100 **Fax:** (479) 756-9919 **Email:** nglide@nanomech.com **URL:** www.nanomech.com

Revision History:

Original Document: 2/21/2018